



COLDSTREAM

Since 1949

SOLID DOOR REACH-IN COOLERS - NON-COLDPACK



Model: RSS RL

RSS

RSS ADVANTAGES

- High volume fans in the cooling area provide even distribution of air, resulting in faster recovery, even product temperatures and shorter run time thereby saving energy.
- Extra capacity refrigeration system that responds to heavy usage and varying ambient temperatures.
- Units use an electronic digital control, complete with high and low temperature alarms and a lockout feature (preventing unauthorized access) that controls temperature, defrosts. Settings are easily changed.
- Low profile cooling coil that maximizes interior space, increasing volume of product that can be stored.

FEATURES:

- All Steel construction, light and strong.
- Doors are full 23 1/2 wide for ease of access.
- Top mounted refrigeration system using environmentally friendly R134A refrigerant. Increase interior space and reduces debris and dirt from attaching to condenser coil decreasing frequency of condenser cleaning
- Door swing can be easily changed with proper replacement hinges, available for a minimal charge
- Durable stainless steel floor - eliminates rust and facilitates easy clean up
- Self-contained condensate removal system eliminates the requirement for an external drain for ease of installation.
- 6" legs standard, casters optional.



proudly manufactured in **CANADA**

www.coldstreamproducts.com

SOLID DOOR REACH-IN COOLERS - LOUVERED TOP - WHITE

Model	ID#	Doors	Shelves	Width	Depth	Height	HP	Amps	Voltage	Refrig.	Weight	List Price
RSS 24 AL (RH or LH)	1668	1	3	23.5"	33.5"	80.25"	1/3	7.2	115	R134a	280lbs	
RSS 48 AL	1708	2	6	48"	33.5"	80.25"	1/2	9	115	R134a	440lbs	

NOTE: White exterior (front & sides) white interior. Non-coldpack model. Allow extra 1 1/2" for handle.

SOLID DOOR REACH-IN COOLERS - LOUVERED TOP - STAINLESS

Model	ID#	Doors	Shelves	Width	Depth	Height	HP	Amps	Voltage	Refrig.	Weight	List Price
RSS 24 RL (RH or LH)	1684	1	3	23.5"	32.25"	80.25"	1/3	7.2	115	R134a	280lbs	
RSS 48 RL	1707	2	6	48"	32.25"	80.25"	1/2	9	115	R134a	440lbs	

NOTE: Stainless exterior (front & sides) white interior. Allow extra 1 1/2" for handle.



Model: RSS RL

MODEL NUMBER DESCRIPTION:

RSS	Reach-in Cooler with split system refrigeration refrigeration is built in cabinet
AL	White Steel Exterior (front & sides) & Interior, coved corner interior. White baked on enamel finish
RL	Stainless Exterior, white steel interior coved corner interior
RH	Right Hand Swing Door
LH	Left Hand Swing Door

This model meets the design criteria of 75° F ambient temperature and humidity of 55% RH - this is the highest offered in the market.

Project name : _____
 Location : _____
 Item #: _____
 QTY: _____